



### Features :

- UK Pin Plug Top
- DOE Level VI Efficiency
- Overcurrent Protection
- Short Circuit Protection
- RoHs Compliant
- 1 Year Warranty
- EN62368 Approved

Model	ECPE-36-05U	ECPE-36-12U	ECPE-36-24U	
<b>Output</b>	DC Voltage	5vdc	12vdc	24vdc
	Rated Current	4amp	3amp	1.5amp
	Current Range	0-4amp	0-3amp	0-1.5amp
	Rated Power	36 Watt	36 Watt	36 Watt
	Ripple & Noise	240mVp-p max	240mVp-p max	240mVp-p max
	Output Regulation	±5%	±5%	±5%
Output Connector	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	
<b>Input</b>	Voltage Range	90-264vac	90-264vac	90-264vac
	Frequency Range	47-63Hz	47-63Hz	47-63Hz
	Input Current	1.2amp Max	1.2amp Max	1.2amp Max
	Inrush Current	40amp Max	40amp Max	40amp Max
	Standby Power	0.1W Max	0.1W Max	0.1W Max
	Leakage Current	0.25amp Max	0.25amp Max	0.25amp Max
	Input Connector	UK	UK	UK
	Operating Temp	0°C~40°C	0°C~40°C	0°C~40°C
<b>Environment</b>	Cooling	Convection	Convection	Convection
	Temperature Coefficient	0.05%/°C	0.05%/°C	0.05%/°C
	Humidity	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)
Storage Temp	-20°C~+80°C	-20°C~+80°C	-20°C~+80°C	
<b>Safety &amp; EMC</b>	Safety Standards	CE EN62368-1		
	EMC Emissions	EN55032,EN55035,		

### Mechanical Specification

